


Swedish optical transmitter 1G



Overview

T1-SFP-1G-SX is a high-performance, cost-effective module with a Duplex LC optics interface, Standard AC coupled CML for high-speed signal, and LVTTTL control and monitor signals. An optical transceiver, also known as a fiber optic transceiver, is a crucial component that facilitates data transmission and reception. The 1000BASE-BX SFP transceiver provides up to 20km of 1000Base-BX throughput over single-mode fibre (SMF) using 1550nm-TX/1310nm-RX wavelengths via LC simplex connectors. 25Gbps and 120km transmission distance with one SMF. The transceiver consists of three sections: a CWDM laser transmitter, a APD photodiode integrated with a trans-impedance preamplifier (TIA) and MCU. Our 1G BiDi SFP transceivers enable full-duplex communication over a single fiber, reducing fiber usage while maintaining reliable performance. Ideal for enterprise networks, data centers, and telecom applications, these modules support long-distance transmission with low power consumption.



Article Content

100G QSFP28 DR1 Optical Transceiver

Optical Transmitter The 100G DR1 optical transceiver electric interface is based on IEEE 802.3 CAUI-4 host to module retimed interface. Optical transmitter/receiver specifications are compliant with 100G

1G SFP Transceivers for Efficient Connectivity

Discover our 1G SFP transceivers, designed for reliable data transmission and seamless connectivity in various networking environments. - EN

Future of Optical Transceivers: A Swedish Telecom Opto View

At Swedish Telecom Opto, we are at the forefront of this evolution, driving innovation in the optical transceiver market. Expanding Horizons ☐☐ The global demand for optical transceivers is experiencing

1G SFP BiDi CWDM 120km Optical Transceivers

The transceiver consists of three sections: a CWDM laser transmitter, a APD photodiode integrated with a trans-impedance preamplifier (TIA) and MCU control unit. All modules satisfy class I laser safety

1G SFP BiDi 1550/1490nm 120km Optical Transceiver

Description The SFP-BIDI transceivers are high performance, cost effective modules supporting dual data-rate of 1.25Gbps/1.0625Gbps and 120km transmission distance with SMF. The transceiver

Optical Transmitters and Receivers : Sources and Its

The optical fiber communication module mainly includes transmitter module like PS-FO-DT as well as receiver module like PS-FO-DR. The communication of fiber

Optical Transceivers

Demystifying Coherent Optics: How Advanced Transceivers are Transforming Data Centers Coherent optics boost data center speed, reach, and efficiency—enabling scalable, high-capacity, and reliable

Swedish Microwave | Quad-Link System

The Swedish Microwave Quad-Link System contains 4x L-Band forward channels + 10 MHz return channel over a single fiber using a direct modulated 1550 nm

Finisar FTLF1318P3BTL | 1G LR Universal SFP

Description Finisar 1G SFP Transceiver Module not only delivers high-performance data transmission over a distance of up to 10km, designed to be highly versatile

1G BiDi SFP | Syrotech

Our 1G BiDi SFP transceivers enable full-duplex communication over a single fiber, reducing fiber usage while maintaining reliable performance. Ideal for enterprise networks, data centers, and telecom

1G SFP Modules: A Deep Dive into Specs & Types

Learn how to choose and optimize 1G SFP modules. Compare specs, fiber vs copper types, troubleshooting tips, and best practices for reliable networks.

A Quick Guide to 1G Optical Transceiver

1G optical module refers to the optical module with a transmission rate of 1.25Gbps. The 1G optical module is already a very mature series of

1G SFP 1310nm 2km Optical Transceiver

The transceiver consists of three sections: a 1310nm FP LD laser transmitter, a PIN photodiode integrated with a trans-impedance preamplifier (TIA) and MCU control unit.

1.6T-FR8 – 1.6T OSFP224 2km Transceiver

1.6Tbps OSFP224 optical transceiver for long-reach applications – up to 2km Product Overview The STC-1.6T-FR8 OSFP224 Optical Transceiver Module, utilizing silicon photonics and EML, features 8

Leading Optical Networking's Future | Swedish Telecom Opto

At Swedish Telecom Opto, we specialize in delivering cutting-edge optical networking solutions for high-performance data centers, cloud infrastructure, and telecom providers. Our innovative products,

1G SFP Optical Transceiver

It has a PIN receiver and a transmitter that uses 850nm VCSEL laser, offering up to 8dB link budget, ensuring seamless 1000Base Ethernet 550m application. We

A Comprehensive Guide to Understanding 1G Optical

1G optical modules play a vital role in modern networking, offering high-speed, reliable, and scalable data transmission. By understanding the

1000BASE BIDI SM SFP 1310/1550nm 20KM

BIDI-1.25G-SFP is Multi-Vendor MSA Compatible SFP (Small Form factor Pluggable) Transceiver, operating over Single Fiber Single-Mode Fiber (SMF) optical cable.

/ 1G Optical Transceivers

Cube Technology Trading's 1G transceiver series offers a diverse portfolio to meet the needs of various network applications, including SONET/SDH, xWDM, Ethernet, Metro Networks, Wireless Networks,

High-Speed Opto Modules

Discover high-performance Opto Modules for reliable and fast data transmission. Explore our range of optical transceivers designed for seamless communication NS - EN

SFP FE/1G OTDR 80km 23dB CWDM-E

The SO-SFP-1G-O-Cxx-E is an SFP form-factor transceiver for OSC (Optical Supervisory Channel) and OTDR (Optical Time Domain Reflectometer)

1G BiDi SFP

GIGALIGHT's 1G BiDi SFP series optical transceiver modules support a speed of 1.25Gbps, widely used in Gigabit Ethernet, 1G fiber channel, and SDH. They can

Generic Compatible 1000BASE-BX-D SFP BiDi 1550nm-TX/1310nm

The 1000BASE-BX SFP transceiver provides up to 20km of 1000Base-BX throughput over single-mode fibre (SMF) using 1550nm-TX/1310nm-RX wavelengths via LC simplex connectors. This bi

1000BASE BIDI SM SFP 1310/1550nm 20KM

This transceiver use top quality FP Laser transmitter with operating at nominal wavelength 1310 nm. and 1550 nm. PIN Photodiode receiver. It support DDM/DOM optical diagnostics, with provide diagnostic

800G-FR4 - OSFP224 2km Transceiver

Add to quote SKU: STC-40017 Categories: 200G 800G 1,6T 800G OSFP SFP CWDM SFP Transceivers 800Gbps OSFP224 optical transceiver module for mid-reach 2km SMF connections

Optics and Transceivers | Fiber Optical Transceivers

FS offers a growing portfolio of optical transceivers, with speed range from 100M, 1G, 10G, 25G, 40G, 50G, 100G, 200G, 400G to 800G and beyond. The fiber

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.saastisfy.fr>

Email: sales@saastisfy.fr

Phone: +33 6 52 81 47 39

Address: 75 Rue de Rivoli, 75001 Paris, France

This document is for informational purposes only. Specifications subject to change without notice.

